

Commercial Rubber



SPECIFICATION SHEET

Grade	N02	
Colour	BLACK	
Elastomer	NR/SBR	
Quality	COMMERCIAL	
Hardness Shore A ± 5	65°	ISO 7619-1
SG (g/cm ²)	1.5	ISO 2781
Tensile (N/mm ²)	3	ISO 37
Elongation %	250	ISO 37
Compression %	43	ISO 37
Tear Strength	10.5	ISO 34-1
Abrasion mm ³		ISO 37
Temperature (°C) from	-20	
Temperature (°C) to	70	

Roll Tolerances

Width tolerance:	+/- 2%	ISO 3302 SW1
Length tolerance:	+/- 2%	ISO 3302 SW1

Thicknesses available

1mm to 6mm	1.4m x10m
8mm to 25mm	1.4m x 5m

Thickness

0.5 1mm	+/- 0.2mm
1.5mm 3mm	+/- 0.3mm
4mm 5mm	+/- 0.4mm
6mm	+/- 0.5mm
8mm	+/- 0.7mm
10mm 15mm	+/- 1mm
20mm	+/- 1.4mm
25mm	+/- 1.75mm

10mm thick available in 1.4m x 5m and 1.4m x 10m
Other thicknesses and sizes available, please contact sales office for your requirements

QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application.
Advice is available but final responsibility remains with the customer.